


BRACINGS ACCORDING TO TIMBER TABLE AND STABILITY OF THE TRUSS SYSTEM SHALL BE DESIGNED SEPARATELY

⊠ INDICATES BRACING




TIMBER:		
CONSTR.-PART	BRACING mm/pcs	LOAD N/m²
1-5	400	400
5-9	400	400
9-1	< 5990	900
2-16	None	
8-11	None	
3-16	None	
7-11	None	
3-14	1 pcs	
7-13	None	
5-13	1 pcs	
5-14	1 pcs	
2-17	None	
8-10	None	
Wedge 1		
Wedge 9		

GENERAL SETTINGS:		
TIMBER THICKNESS: (mm)		3 x 45
TRUSS CENTRES: (mm)		2400
CLIMATE CLASS:		2
BRACING: SEE TIMBER TABLE		
LOADS (N/m²):		
SNOW LOAD (BASE VALUE):		1750
WIND LOAD (BASE VALUE):		595
LIVE LOAD:	NO	FREE
	1	500
DEAD LOADS: SEE TIMBER TABLE		
OTHER LOADS AS PER CALC. PRINT-OUT		

GENERAL DIRECTIONS:

THE STRUCTURE HAS BEEN CALCULATED USING
COMPUTER PROGRAM "TRUSSCON". LIC.NO: 15411
CODE TIMBER: LVS-EN 1995-1-1 + NA
LOADS: LVS-EN 1991 + NA
FULL DESIGN RESULTS AS PER CALC. PRINT-OUT

VERSION: 2017
TIME: 14.22

			SCALE 1:45		
DRAWN CONSTR.BY	CHECKED	JOB NO.			
20170727		T4			
			CODE TYPE NO.	DRAWING NUMBER	REG.
				T4	